

<p>Product composition</p>	<p>Characteristics</p> <p style="text-align: right;">1</p>	
	<ul style="list-style-type: none"> ▶ Pyroguard EW30 Impact is cuttable with standard equipment ▶ Available in stock sheets 1580 x 2780 mm ▶ Installation interior and exterior (UV stable) ▶ Double sided fire resistance 	
<p>Technical characteristics</p>	<p>Physical features</p>	
<ul style="list-style-type: none"> ▶ Fire classification: EW30 ▶ Impact classification: 2B2 ▶ Light transmission: 87% ▶ Sound reduction: 33 dB ▶ U value: 5.1 W/m² K ▶ UV stability: yes 	<ul style="list-style-type: none"> ▶ Nominal Thickness: 7 mm ▶ Thickness tolerances: - 0.6 / + 0.8 mm ▶ Weight/m²: 17 kg ▶ Temperature range: - 20 / + 140 °C ▶ Min manufactured size: 	
	<p>Possible applications</p>	
<p>FLEXIBLE INDEPENDENT RESPONSIVE SPECIFIC TECHNICAL FIRST IN FIRE GLASS</p>	<p>Steel system</p> <p>Timber system</p> <p>Please see PV 12-A-422, page 90</p> <p>Please see PV 12-A-423, page 91 & 92</p> <p>CF 257 p 18</p>	
<p>28</p> <p>06/2015</p>	<p>The diagrams in this document are for guidance purpose only, for actual projects specific drawings are required.</p>	