

<p>Product composition</p>	<p>Characteristics</p>	6
	<ul style="list-style-type: none"> ▶ Internal and external installation (UV stable) ▶ Spacer bar in steel or aluminium from 6 to 15 mm with the possibility to add argon gas ▶ Float, toughened or laminated counter panes 	
<p>Technical characteristics</p>	<p>Physical features</p>	
<ul style="list-style-type: none"> ▶ Fire classification: EW30 ▶ Impact classification: DC ▶ Light transmission: DC ▶ Sound reduction: DC ▶ U value: DC ▶ UV stability: yes 	<ul style="list-style-type: none"> ▶ Nominal Thickness: DC ▶ Thickness tolerances: DC ▶ Weight/m²: DC ▶ Temperature range: – 20 / + 140 °C ▶ Min manufactured size: 	
<p>Possible applications</p>		
<div style="display: flex; flex-direction: column; align-items: flex-start;"> <div style="margin-bottom: 20px;"> <p>Steel system</p> </div> <div style="margin-bottom: 20px;"> <p>Timber system</p> <p>Please see PV 12-A-422, page 90</p> </div> <div style="margin-left: 150px;"> <p>Please see PV 12-A-423, page 91 & 92</p> </div> </div>	<p>FLEXIBLE INDEPENDENT RESPONSIVE SPECIFIC TECHNICAL FIRST IN FIRE GLASS</p>	
		<p>06/2015 33</p>

The diagrams in this document are for guidance purpose only, for actual projects specific drawings are required.