

<p>Product composition</p>	<p>Characteristics</p> <p style="text-align: right; background-color: #e67e22; color: white; padding: 5px;">8</p>
	<ul style="list-style-type: none"> ▶ Internal and external installation (UV stable) ▶ Spacer bar in steel or aluminium from 6 to 12 mm with the possibility to add argon gas ▶ Float, toughened or laminated counter panes
<p>Technical characteristics</p>	<p>Physical features</p>
<ul style="list-style-type: none"> ▶ Fire classification: EW60 ▶ Impact classification: DC ▶ Light transmission: DC ▶ Sound reduction: DC ▶ U value: DC ▶ UV stability: yes 	<ul style="list-style-type: none"> ▶ Nominal Thickness: DC ▶ Thickness tolerances: DC ▶ Weight/m²: DC ▶ Temperature range: – 20 / + 140 °C ▶ Min manufactured size:
<p>Possible applications</p>	
<p>Steel system</p> <p>Timber system</p> <p>Please see PV 07-V-249, page 93</p>	<p style="text-align: center; font-weight: bold; letter-spacing: 0.5em;">F L E X I B L E I N D E P E N D E N T R E S P O N S I V E S P E C I F I C T E C H N I C A L FIRST IN FIRE GLASS</p>
<p style="text-align: right;">06/2015 35</p>	

The diagrams in this document are for guidance purpose only, for actual projects specific drawings are required.