

<p>Product composition</p>	<p>Characteristics</p> <p style="text-align: right;">12</p>
<p>Labels: Float, Silicate, PVB layer</p>	<ul style="list-style-type: none"> ▶ Cuttable with specialist equipment ▶ External installation ▶ Double sided fire resistance ▶ Excellent impact rating ▶ Large tested sizes ▶ EI30 - E60 applications
<p>Technical characteristics</p>	<p>Physical features</p>
<ul style="list-style-type: none"> ▶ Fire classification: EI30 ▶ Impact classification: 1B1 ▶ Light transmission: 85% ▶ Sound reduction: 38 dB ▶ U value: ▶ UV stability: 	<ul style="list-style-type: none"> ▶ Nominal Thickness: 19 mm ▶ Thickness tolerances: ▶ Dimensional tolerances: ▶ Weight/m²: DC ▶ Temperature range: ▶ Stock sheet size: 3100 x 2125 mm ▶ Min manufactured size:
<p>Possible applications</p>	
<p>Steel system</p> <p>Timber system</p>	<p style="text-align: center;"> F L E X I B L E I N D E P E N D E N T R E S P O N S I V E S P E C I F I C T E C H N I C A L FIRST IN FIRE GLASS </p>
<p style="text-align: right;">06/2015 39</p>	

The diagrams in this document are for guidance purpose only, for actual projects specific drawings are required.