

<p>Product composition</p>	<p>Characteristics</p> <p style="text-align: right;">13</p>
<p style="text-align: center;">Pyroguard EI30 EXT</p>	<ul style="list-style-type: none"> ▶ External installation ▶ Excellent impact rating ▶ Large tested sizes ▶ EI30 - E60 applications ▶ External applications
<p>Technical characteristics</p>	<p>Physical features</p>
<ul style="list-style-type: none"> ▶ Fire classification: EI30 ▶ Impact classification: 1B1 ▶ Light transmission: DC ▶ Sound reduction: 40 dB ▶ U value: DC ▶ UV stability: yes 	<ul style="list-style-type: none"> ▶ Nominal Thickness: DC ▶ Thickness tolerances: ▶ Dimensional tolerances: ▶ Weight/m²: DC ▶ Temperature range: ▶ Min manufactured size:
<p style="text-align: center;">13</p>	<p>Possible applications</p>
<p style="text-align: center;"> F L E X I B L E I N D E P E N D E N T R E S P O N S I V E S P E C I F I C T E C H N I C A L FIRST IN FIRE GLASS </p>	<p>Steel system</p> <p>Timber system</p>
<p>40 06/2015</p>	

The diagrams in this document are for guidance purpose only, for actual projects specific drawings are required.