

<p>Product composition</p>	<p>Characteristics 45</p>
<p style="text-align: center;">Pyroguard T-EI30/32-2 SWS</p>	<ul style="list-style-type: none"> ▶ Fire resistant buttjoint glass for 30 minutes, comprising a middle pane which is float glass and two exterior panes which are laminate 44.2 and 2 silica gel interlayers ▶ Spacer bar in steel or aluminium from 6 to 18 mm with the possibility to add argon gas (depending on recommendations in the test report) ▶ Counter panes: <ul style="list-style-type: none"> - float, toughened or laminated glass - security option - decorative glass (satin, mirrored, screen print) - low emissivity glass - solar control (depending on recommendations in the test report)
<p>Technical characteristics</p>	<p>Physical features</p>
<ul style="list-style-type: none"> ▶ Fire classification: EI30 ▶ Impact classification: DC ▶ Light transmission: DC ▶ Sound reduction (c; ctr): DC ▶ U value: DC ▶ UV stability: yes 	<ul style="list-style-type: none"> ▶ Nominal Thickness: DC ▶ Thickness tolerances: DC ▶ Dimensional tolerances: ± 3 mm ▶ Weight/m²: DC ▶ Temperature range: – 10 / + 45 °C ▶ Min manufactured size: 300 x 400 mm
<div style="background-color: yellow; width: 40px; height: 20px; margin: 0 auto;"></div>	<p>Possible applications</p>
<p style="text-align: center;"> F L E X I B L E I N D E P E N D E N T R E S P O N S I V E S P E C I F I C T E C H N I C A L FIRST IN FIRE GLASS </p>	<p style="text-align: center;"> Timber system </p> <p style="text-align: right;">Please see PV 13-A-426 ext. 10/1, page 103</p>
<p>72 06/2015</p>	

The diagrams in this document are for guidance purpose only, for actual projects specific drawings are required.