

# Declaration of Performance



DOP # 21

06/01/2022



Marking of Pyroguard

**T-EW30/6 TVI RV**

Pyroguard UK Ltd., Millfield Lane, Haydock, Merseyside. WA11 9GA.  
Tel.: +44 (0) 1942 710 720

We declare under sole responsibility, the following characteristics for the CE Marking and UKCA marking of this glass product, intended to be used in building and construction works, following product standard stated below :

| Manufacturing Site |  | Seinghouse, UK; Oldbury, UK   |                      |
|--------------------|--|---|----------------------|
| Notified Body      |  | Efectis, FR 1812  |                      |
| Product Standard   |  | EN12150-2 Toughened safety glass<br>EN1279-5+A2 Insulating glass units. |                      |
| Characteristics    |  | AVCP System(s)  | Declared Performance |
| 1                  | Resistance to fire (EN 13501-2)  | 1   | EW30                 |
| 2                  | Reaction to fire (EN 13501-1)  | 3, 4  | NPD                  |
| 3                  | External fire performances (EN13501-5)   | 3, 4  | NPD                  |
| 4                  | Bullet resistance (EN 1063)  | 1   | NPD                  |
| 5                  | Explosion resistance (EN 13541)  | 1   | NPD                  |
| 6                  | Burglar resistance (EN 356)  | 3   | NPD                  |
| 7                  | Pendulum body impact resistance (EN 12600)                                     | 3   | 1C1                  |
| 8                  | Resistance against sudden temperature change and temperature differentials (K) | 4   | NPD                  |
| 9                  | Wind, snow, permanent and imposed load resistance (mm)                         | 4   | 40                   |
| 10                 | Direct air borne sound reduction (EN 12758): Rw (C;Ctr)                        | 3   | 35 (-1;-5)           |
| 11                 | Heat transfer coefficient (EN 673) : Ug  | 3   | 0,84                 |
| 12                 | Normal emissivity En coated side (EN 12898)                                    | 3   | NPD                  |
| 13                 | Light transmission (EN 410): Tv  | 3   | 62                   |
| 14                 | Light reflection outside (EN 410) : Dv   | 3   | 0,23                 |
| 15                 | Light reflection inside (EN 410) : D'v   | 3   | 0,23                 |
| 16                 | Total energy transmission factor (EN 410) : g                                  | 3   | 0,58                 |
| 17                 | Direct radiation transmission factor (EN 410): Te                              | 3   | 0,47                 |
| 18                 | Direct radiation reflection factor outside (EN 410) : De                       | 3   | 0,19                 |
| 19                 | Direct radiation reflection factor inside (EN410) : D'e                        | 3   | 0,19                 |
| 20                 | Ultraviolet transmittance (EN 410) : Tuv                                       | 3   | 0,25                 |
| 21                 | General colour rendering index (CRI) : Ra                                      | 3   | 99                   |
| 22                 | Durability (EN ISO 12543-4)  | 3, 4  | YES                  |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer in Seinghouse, France by:

Dr Vincent Crook (Director of Technical Development, Pyroguard UK Ltd)

| Author    |                           | Validation                        |  |
|-----------|---------------------------|-----------------------------------|--|
| Name      | Mr Simon Ellison          | Dr Vincent Crook                  |  |
| Function  | Technical Support Manager | Director of Technical Development |  |
| Date      | 06/01/2022                | 06/01/2022                        |  |
| Signature | SEI                       | ViCr                              |  |